

A **nochar** ENVIRONMENTAL PROTECTION PRODUCT 

nochar's P215TM

Plumbers, welders, or anyone using a torch can use **nochar's P215** heat barrier paste. **nochar's P215** will minimize direct or radiant heat transfer from the torch to adjoining surfaces.

Asbestos free **P215** can be used on natural or synthetic surfaces adjoining the welding or soldering areas such as PVC drains, wood trim, plastic or vinyl cabinets. Heat sensitive surfaces can be temporarily coated during the soldering process and then easily cleaned by wiping the **P215** off. **P215** is water soluble and therefore can be removed with just a damp cloth.

nochar's Environmental Protection Products include spill control and bonding agents; heat barriers; fire retardant additives for foam manufacturing; fire retardant sealers for flexible and rigid foams, fabrics, and previously-sealed surfaces; and an unique extinguishing system for petroleum-based fires. See your **nochar** representative for additional information.

P215 Fact Sheet

WEIGHT BY VOLUME

SPREAD RATE

SPECIFIC GRAVITY

PH SPECIFICATIONS

STORAGE

VOLATILITY BEFORE USE

VOLATILITY AFTER USE

DISPOSAL

PACKAGING

TOXICITY

NOTICE

1/2 Gallon equals 70 oz.

1/4" or more, depending on protection needed.

1.09

Neutral

Keep container sealed to prevent evaporation; keep from freezing.

None

None

Water soluble; rinse with water

1/2 Gallon resealable containers

Non-Toxic, Non-Hazardous, Non-Corrosive

All statements, technical information and recommendations contained herein are based on information and tests we believe to be reliable. The accuracy or completeness thereof are not guaranteed.